


# **EcoGreen Solar Shades, LLC.**

www.EcoGreenSolarShades.com • (440) 232-1551 • Toll Free: 877-610-1555



## **Avila Twilight**



SC (Internal)



### **Specifications**

**Product Type:** Interior - Blackout **Width:** 110" (280cm)

**Composition:** 100% Polyester / Acrylic **Weight:** 14.5 oz / yd2 (490 g / m2)  $\pm$  7%

Foamed Backing / PVC Free **Thickness:**  $.020'' (0.52 \text{ mm}) \pm 5\%$ 

Standard Packaging: Rolls of 30 ly (27 lm) Yarn Count: Warp / 66 Weft / 33 (ends per inch)

Fabric is treated with Duraguard® Fabric Protector to resist most stains and SANITIZED® Antimicrobial Protection

to resist most molds and mildew.

**Fenestration Properties:** Openness Factor\* 0% UV Blockage: 100%

						SC (Internal)	
Item#	Style Name	Ts	Rs	As	Tv	1/4" CI	1/4" HA
0002	White	0	65	35	0	0.30	0.30
0030	Black	0	64	36	0	0.31	0.31

Similar fenestration data achieved for all colors.

00.20 Linen, 00.52 Olive, 00.01 Slate Grey, 00.61 Chocolate, 00.15 Khaki, 00.07 Pearl

Solar Transmittance (Ts), Solar Reflectance (Rs), Solar Absorptance (As), Visible Light Transmittance (Tv) and Openness Factor (OF), Shading Coefficient (SC), Clear Plate (Cl), Heat Absorbing, Plate (HA).

The fenestration property tests were conducted in accordance with ASHRAE Standard 74-1988 "Methods of Solar Optical Properties of Materials". The above data is indicative.
For current test results, performance specifications and larger samples, contact the Mermet Marketing Department.

#### **Applications:**







Roller Shades

Roman Shades

n Snades

Fire Classifications:

NFPA 701-2004 TM#1, California U.S. Title 19.

#### **Fabrication Methods:**

- Cutting: Cold Cut, Ultrasonic, Crush Cut, or Laser
- Seaming / Hemming: Thermal, High-Frequency, Ultrasonic, or Sewing

#### **Care and Cleaning:**

Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating of the fabric. Clean with a sponge or a soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also rub the fabric very gently with a clean white pencil eraser to remove small stains.



Ken Herman, President Ken@EcoGreenSolarShades.com www.EcoGreenSolarShades.com

Phone: 440-232-1551 Fax: 440-232-1122 Toll Free: 877-610-1555

EcoGreen Solar Shades, LLC 7603 First Place B7 Oakwood Village, OH 44146